

Features:

- In conformity with ISS : 1709 requirements and can be applied to 50Hz~60Hz AC power system.
- Construction type: Oil-Filled, Jelly filled, dry encapsulated. Product Features: small in dimension, light in weight, low dissipation factor, good self-healing character and especially safety reliability. Widely applied to Ceiling Fans, Table Fans, Split AC Blower Motors, etc.
- **Specification: power rating: 300~350~400~440 VAC, Capacitance range:1.5~5.0μF**
Dissipation Factor<=0.002 (50Hz)
Discharge performance: <50V after breakage in 60 seconds at $\sqrt{2}U_n$.
- **Voltage under steady state: run under 1.1Un**
Current under steady state: run under 1.5In
Climatic category: -25°C~85°C

Special requirements can be fulfilled at the request of customers.

Rate Voltage (VAC)	Standard capacity (μF)	Outline Dimensions (Only for Round Cans)		
		D (mm)	H (mm)	Remark
300~440	1.5	25	50	PPW & PPT Series
	1.75			FLW & FLT Series
	1.85			OF, ADW, ADT, PPW & PPT Series
	2.00			
	2.25	25/27/30	50/52/52	
	2.5			
	3.0	27/30	52	
	3.5	30/35	52	ADW, ADT, PPW & PPT Series
	4.0			FLW & FLT Series
	5.0			